

## **Description:**

Inline silicone coated release liner Pet film


Features and applications:

- \* One side inline silicone coated
- \* Minimum silicone rub-off

- \* Excellent slip and good dimensional stability
- \* Ultra thin, highly cured, minimum smear effect

Available gauge(s) (µm): 12,23,36

PRS needs to be stocked in a closed warehouse and preserved from the light. Polinas will not accept any responsibility for material older than 1 year from the delivery It is recommended to use with acrylic base adhesives



Properties	Unit		Technical Values			Test Method
Thickness	μm		12	23	36	ASTM D 2673
Yield	m2/kg		59,9	31,3	20	ASTM D 2673
Haze	%		=< 5	=< 5	=< 5	ASTM D 1003
Dimensional stability	%	MD	=< 1,5	=< 1,5	=< 1,5	ASTM D 1204
	%	TD	=< 1	=< 1	=< 1	
Tensile strength at break	kg/mm²	MD	23	23	23	ASTM D 882
	kg/mm²	TD	24	24	24	
Elongation	%	MD	130	130	130	ASTM D 882
	%	TD	120	120	120	
Release force	g/in		< 15	< 15	< 15	POLINAS

## F: Front B: Back

This film complies with the EC and FDA food contact regulations. Detailed documentation is available on your request. All the information contained in this datasheet is supplied at the best of our knowledge and must not be construed as a guarantee. Since the circumstances and processes used in the application of our product are beyond our control, our guarantee remains within the limits of the generic conditions of supply of the product itself. Business Development and Customer Solutions Department is available to supply upon request all the updated recommendations relevant to the best converting and processing techniques for the product. Also, different film thicknesses and properties are available upon request.









**Date** : 27.02.2024

Main Plant : Organize Sanayi Bölgesi, Manisa 45030 - Tel : +90 236 226 22 00 (pbx) Fax : +90 236 233 25 25 e-mail : info@polinas.com.tr Istanbul Office : Kısıklı Mah., Alemdag Cad. No:60 Masaldan s Merkezi, F Blok Kat:1, 34692 Üsküdar / stanbul 34692 - Tel: +90 850 209 19 00 Fax: +90 236 233 25 25