

**SAFETY DATA SHEET**

According to Regulation (EU) 2015/830 and Regulation (EC) No 1907/2006

Product Name	Biaxially Oriented Polyethylene Terephthalate (BOPET) Film	Print Date	12.04.2005
		Revision Date	13.04.2022
		Revision No	3
		Page No	1 / 10

**SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1. Product Identifier**

Trade Name POLIPET  
Chemical Classification Polyester  
Product Description Polymer Article/ Packing Material/ Labeling Material & Associated Applications

**1.2. Relevant identified uses of the substance or mixture and uses advised against:****Relevant identified uses:**

POLIPET Coated, biaxially oriented polyethylene terephthalate film (BOPET)

**1.3. Details of the supplier of the safety data sheet**

Manufacturer/Supplier POLINAS PLASTİK San. ve Tic. A.Ş.  
Address Organize Sanayi Bölgesi, Cumhuriyet Cad. No: 2-26  
45030  
MANİSA/TÜRKİYE  
Telephone Number +90 236 226 22 00  
Fax Number +90 236 233 25 25  
E-Mail of Competent person responsible for the SDS [damla.erdis@polinas.com.tr](mailto:damla.erdis@polinas.com.tr)

**1.4. Emergency telephone number**

Emergency telephone No: +90 236 226 22 00 (Dahili 332)  
UZEM 114 (National Poison Information Center)

**SECTION 2. HAZARDS IDENTIFICATION****2.1. Product classification**

This product is not classified as dangerous under Regulation (EC) No 1272/2008.  
This product according 1907/2006/EC not classified as hazardous.

**2.2. Label elements**

Not necessarily the product to be labeled in accordance with EC regulations or the national laws.

**2.3. Other hazards**

The molten polymer adheres to the skin and may cause burns. Slipping hazard may occur if spilled material is present. Be aware of electrostatic charging when used.

**3. SECTION 3. COMPOSITION/ INFORMATION ON INGREDIENTS****3.1. Substances**

Substances / Ingredient	CAS / EC No.	%	Classification
Polyetilen Tereftalat	CAS No: 25038-59-9 EC No: 618-352-4	>99-99,8	NA

**SAFETY DATA SHEET**

According to Regulation (EU) 2015/830 and Regulation (EC) No 1907/2006

<b>Product Name</b>	<b>Biaxially Oriented Polyethylene Terephthalate (BOPET) Film</b>	<b>Print Date</b>	<b>12.04.2005</b>
		<b>Revision Date</b>	<b>13.04.2022</b>
		<b>Revision No</b>	<b>3</b>
		<b>Page No</b>	<b>2 /10</b>

*THE FOLLOWING FILLERS AND ADDITIVES CAN BE PRESENT*

Maddeler/ Bileşen	CAS / EC No.	%	Classification
Polyurethane resin (polyester type)	CAS No: 39323-37-0	<0,6	NA
Synthetic Amorphous Silica	CAS No: 7631-86-9	<0,2	NA
Diantimony trioxide	CAS No: 1309-64-4 EC No: 215-175-0	<0,1	NA
Aluminum	CAS No: 7429-90-5 EC No: 231-072-3	< 0,02	NA

**3.2. Mixtures**

No data available

---

**SECTION 4. FIRST AID MEASURES**

---

**4.1. Description of first aid measures****Eye Contact**

Dust, process, polymer vapors and fine dust of the substance can irritate the eyes. In case of exposure to hot molten material; Cold water should be applied to the affected area. Check for contact lenses and remove contact lenses. Immediately flush eyes for at least 15 minutes holding eyelids open. seek medical help.

**Skin Contact**

In case of skin contact, wash with water. If irritation occurs, seek medical attention. Serious burns may occur in case of contact with molten material. In case of contact with molten material, immediately flush skin with large volumes of cold or ice water for at least 15 minutes. Do not try to remove adhered material from the skin, it may seriously damage the skin. Seek immediate medical attention.

**Inhalation**

Vapors and fumes generated by the combustion or heating of the material may irritate the respiratory tract. In such a case, the patient should be taken to the open air immediately. Seek immediate medical attention.

**Ingestion**

Seek medical attention immediately. To avoid danger of suffocation, keep away from the head area and children. Ingestion may cause irritation to the mouth and throat area and the digestive tract. Do not force vomiting. Seek medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No additional information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No specific treatment.

---

**SECTION 5. FIREFIGHTING MEASURES**

---

**5.1. Extinguishing media**

CO<sub>2</sub>, Halon, AFFF (Aqueous Film-Forming Foam) Foam, water spray (mist) only to cool the surfaces exposed to the fire.

**SAFETY DATA SHEET**

According to Regulation (EU) 2015/830 and Regulation (EC) No 1907/2006

<b>Product Name</b>	<b>Biaxially Oriented Polyethylene Terephthalate (BOPET) Film</b>	<b>Print Date</b>	<b>12.04.2005</b>
		<b>Revision Date</b>	<b>13.04.2022</b>
		<b>Revision No</b>	<b>3</b>
		<b>Page No</b>	<b>3 /10</b>

**5.2. Special hazards arising from the substance or mixture**

Complete combustion with an excess of oxygen forms; CO<sub>2</sub> and water vapor. Partial combustion forms also; CO, fumes and vapors irritating to the respiratory tract.

**5.3. Advice for firefighters**

Prevent the spread of fire. The fire brigade should be notified immediately. Excess personnel should be removed from the fire scene. Persons in charge of extinguishing the fire should have special protective clothing, goggles, personal oxygen cylinders. Appropriate respirators should be worn where there is a risk of exposure to harmful vapors or fumes from the material. Pressurized water should not be used as it may cause the fire to spread.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures**

Film reels and pallets are very heavy. The edges of the film are sharp and can cause cuts and injuries. Protective equipment should be used during use. Before handling molten material, wear protective gloves. Move it off the floor immediately as slippery material can cause falls and accidents. Check that the grounding of all equipment in the place where the material is working is done correctly. If there is a risk of fire where the material is located, remove personnel and report a fire immediately. Personnel who will respond to the fire should wear suitable heat-resistant protective clothing. Avoid breathing mists and vapor. Keep people who do not take protective measures away. Wear full protective goggles in dusty environments.

**6.2. Environmental Precautions**

Do not allow material to enter drains and surface waters. Collect the material for recovery and send it to recovery facilities. If recycling is not possible, dispose of it according to the methods described in Section 13 "Disposal Information". Notify the environmental agency.

**6.3 Methods and material for containment and cleaning up**

It should be stored in its original package at ambient conditions (25 °C, 50% relative humidity). The material should be away from heat sources in the stock environment, static electricity should be prevented. If stocking is to be done on the shelf arrangement, fixing should be done. The film on the floor can cause slips. This material, which is on the floor and may cause falls, should be removed from the environment by sweeping. Dispose of waste product in accordance with local and national laws/regulations.

**6.4. Reference to other sections**

See section 4.

---

**SECTION 7. HANDLING AND STORAGE**

---

**7.1. Precautions for safe handling**

Precautions should be taken against the possibility of the rolls falling and overturning. Protective work shoes and other protective clothing should be worn during roll lowering and lifting. When transporting the rolls on the pallet, make sure that there are supporting wedges on both sides. Do not roll the rolls from one place to another. For this, the rolls must be transported by forklift, fixed on the pallet with wedges and strips. Precautions should be taken against static electricity and dusting. Rolls of film wrapped with cling film (or similar) should be unrolled away from a solvent, chemical or similar potential source of ignition and outside the process area.

**7.2. Conditions for safe storage, including any in compatibilities**

## SAFETY DATA SHEET

According to Regulation (EU) 2015/830 and Regulation (EC) No 1907/2006

<b>Product Name</b>	<b>Biaxially Oriented Polyethylene Terephthalate (BOPET) Film</b>	<b>Print Date</b>	<b>12.04.2005</b>
		<b>Revision Date</b>	<b>13.04.2022</b>
		<b>Revision No</b>	<b>3</b>
		<b>Page No</b>	<b>4 / 10</b>

Store in dry, dust-free area and on the pallets. Keep away from sunlight. Ventilation must be supplied in existence of melting processes. Use proper grounding procedures to avoid static electric. Storage area should be equipped with appropriate extinguishing capability (e.g. sprinkler system, portable fire extinguishers, flammable gas detectors).

### 7.3. Specific end use(s)

No data available

## SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### 8.1. Control parameters

Eyewash and safety shower should be nearby and ready for use. In case of failure of process equipment, safety showers and eye washes should be located close to the chemical exposure area. Use in a well-ventilated area.

### Exposure limits / standards

This mixture contains exposure values for the following ingredients in pure form:

Exposure Limits	ACGIH TWA/STEL	OSHA PEL/STEL
Polyethylene Terephthalate	NA	NA
Synthetic Amorphous Silica	2.4 mg/m <sup>3</sup> (Respirable Dust) 6 mg/m <sup>3</sup> (Total Dust)	NA
Antimony Trioxide	0.5 mg/m <sup>3</sup>	0,5 mg/m <sup>3</sup>
Aluminum	1 mg/m <sup>3</sup>	5 mg/m <sup>3</sup> (Respirable Dust) 15 mg/m <sup>3</sup> (Total Dust)

### 8.2. Exposure controls

#### 8.2.1 Appropriate engineering control

Not information available

#### 8.2.2. Personal Protection equipment

There should be a ready-to-use safety and eyewash nearby. Do not drink, eat or smoke where the material is handled. Film layers can create slipperiness on the floor. This must be gained in the habit of being careful all over the floor.

##### 8.2.2.1. Eye and Face Protection

Safety glasses is recommended. Eyewash fountains and safety showers should be easily accessible.

##### 8.2.2.2. Skin/Hand/Feet Protection

Protective shoes, gloves and clothes are recommended. Do not eat, drink or smoke in areas where this material is handled. If there is a risk of contact with hot molten material, wear safety shoes, protective gloves and protective clothing with heat insulation and protection against chemicals.

##### 8.2.2.3. Respiratory Protection

Where there is a risk of exposure to dust, steam and smoke may be generated by thermal decomposition of the material. In this case, a suitable ventilation system should be established in the area where the coating unit is located and in the working area. Thermal degradation of PVDC in PVDC coated films releases HCl gas. In case of exposure above the specified standards, a respiratory protection program in accordance with the 1910.134 OSHA General Industry Standard should be applied. If vapors are detected, use MSHA/NIOSH-accepted full-face respirator.

**SAFETY DATA SHEET**

According to Regulation (EU) 2015/830 and Regulation (EC) No 1907/2006

<b>Product Name</b>	<b>Biaxially Oriented Polyethylene Terephthalate (BOPET) Film</b>	<b>Print Date</b>	<b>12.04.2005</b>
		<b>Revision Date</b>	<b>13.04.2022</b>
		<b>Revision No</b>	<b>3</b>
		<b>Page No</b>	<b>5 /10</b>

**8.2.3. Environmental exposure controls**

No information available.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

---

**9.1. Information on basic physical and chemical properties**

a) Appearance	PET film
b) Colour	Transparent or metallized.
c) Odour	Odorless
d) Odour Threshold	Not Applicable
e) Boiling Point Range	Not Applicable
f) Melting Point Range	260 °C
g) Density (20°C)	1400 kg/m <sup>3</sup>
h) Vapor Pressure (20°C de hPa)	Not Applicable
i) Explosion Limits (in air)	Not Applicable
j) Solubility (20°C de (mg/l))	Not soluble in water

**9.2. Other information**

No information available.

---

**10. STABILITY & REACTIVITY**

---

**10.1. Reactivity**

Stable under normal conditions.

**10.2. Chemical stability**

This product is stable under normal conditions of use.

**10.3. Possibility of hazardous reactions**

May react with strong oxidants and strong acids. Use of the material can generate electrical charges and sparks that can ignite other combustible materials. In PVDC coated films, the products of thermal degradation are HCl, CO, and C particles.

**10.4. Conditions to avoid**

Heat, sparks, flames are sources that should be avoided. Contact or proximity to flame or spark should be avoided. It should not be heated to temperatures exceeding 235°C. Do not allow dust formation in the working place. Prevent static electricity, make grounding. Strong static electricity may occur during the roll film processing, do not allow dust and explosive air mixtures to form in the working area.

**10.5. Incompatible materials**

Fluorinated and oxygenated compounds. Avoid storage or contact with strong oxidizing agents, strong acids and alkalis.

**10.6. Hazardous decomposition products**

Hazardous polymerization will not occur. Carbon Monoxide, Carbon Dioxide, selected alkenes and aldehydes including acrolein and formaldehyde can be formed in negligible amount.

**SAFETY DATA SHEET**

According to Regulation (EU) 2015/830 and Regulation (EC) No 1907/2006

Product Name	Biaxially Oriented Polyethylene Terephthalate (BOPET) Film	Print Date	12.04.2005
		Revision Date	13.04.2022
		Revision No	3
		Page No	6 /10

**SECTION 11. TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

It contains the toxicity values of the following components in pure form in this mixture. The product has not been tested. The information given is derived from the properties of the individual components.

Toxicity	Inhalation LC 50	Dermal LD 50	Oral LD 50
Polyethylene Terephthalate	Not available	Not available	Not available
Synthetic Amorphous Silica	>0.139 mg/l / 14h (Rat)	>5000mg/kg (Rabbit)	>10000 mg/kg (Rat)
Diantimony trioxide	>5,2 mg/l /4h (Rat)	>8.300mg/kg (Rabbit)	>34000 mg/kg (Rat)
Aluminum	Not available	Not available	Not available

**Chronic Toxicity**

Based on our experience and available information, no harmful health effects are expected if the product is used as recommended, with appropriate precautions for the identified uses. Emissions at high temperatures can damage the respiratory organs.

**Chronic Toxicity - Carcinogenic Effects**

Diantimony trioxide\* (1309-64-4) ; IARC Classification : Group 2B – Possibly Carcinogenic to humans. ACGIH considers the substance Diantimony trioxide to be a suspected human carcinogen.

**(a) Eye contact:**

No specific data.

**(b) Skin contact**

No specific data

**(c) Inhalation**

No specific data

**(d) Ingestion**

No specific data

**12. EKOLOJİK BİLGİLER****12.1. Toxicity**

There is no evidence report that the material has environmental risk.

**12.2. Persistence and degradability**

Very low level UV deterioration.

**12.3. Bioaccumulative potential**

This material is not expected to be readily biodegradable.

**12.4. Mobilty of Soil**

Not available

**12.5. Result of PBT and vPvB assesment**

Not applicable

**12.6. Other adverse effects**

No information available

**12.7. Additional information**

No information available

## SAFETY DATA SHEET

According to Regulation (EU) 2015/830 and Regulation (EC) No 1907/2006

<b>Product Name</b>	<b>Biaxially Oriented Polyethylene Terephthalate (BOPET) Film</b>	<b>Print Date</b>	<b>12.04.2005</b>
		<b>Revision Date</b>	<b>13.04.2022</b>
		<b>Revision No</b>	<b>3</b>
		<b>Page No</b>	<b>7 /10</b>

---

### SECTION 13. DISPOSAL CONSIDERATIONS

---

#### 13.1. Waste treatment methods

##### Waste product

It can be recycled. If recycling is not possible, waste must be disposed of in accordance with national and regional control regulations. It should not be attempted to be disposed of by incineration in an uncontrolled manner. The same procedure applies to contaminated packing waste.

---

### SECTION 14. TRANSPORT INFORMATION

---

#### 14.1. UN Number

**UN Number** Not applicable

#### 14.2. UN Proper Shipping Name

**Shipping Name** Not applicable

#### 14.3./14.4./14.5. Transport Hazard Class(es)/Packing Group/Environmental Hazards

**ADR/RID/ADNR Regulation** It is not classified as hazardous substance in under current transportation regulation

**IMDG ( Marine Transportation )** It is not classified as hazardous substance in under current transportation regulation

**ICAO/IATA** It is not classified as hazardous substance in under current transportation regulation

#### 14.6. Special Precautions For User

Not required

#### 14.7. Transport in Bulk According to Annex II MARPOL 73/78 and the IBC Code

Not applicable

---

### 15. REGULATORY INFORMATION

---

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Classification and Labeling According to regulation EU CLP 2008 (1272/2008/EC)

EU regulation Classification and labeling have been determined according to EU Directive 67/548/EEC, 1999/45/EC (including amendments) and (EC) No. 1907/2006 Regulation take into account the intended product use.

#### 15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

---

### SECTION 16. OTHER INFORMATION

---

OSHA	Occupational Safety Health Administration
PEL	Permissible Exposure Limit
ACGIH	American Conference of Governmental Industrial Hygienists
TLV	Threshold Limit Value
STEL	Short Term Exposure Limit
TWA	Time-Weighted Average
IMO	International Maritime Organization
IATA	International Air Transport Association
ICAO	International Civil Aviation Organization
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)

**SAFETY DATA SHEET**

According to Regulation (EU) 2015/830 and Regulation (EC) No 1907/2006

<b>Product Name</b>	<b>Biaxially Oriented Polyethylene Terephthalate (BOPET) Film</b>	<b>Print Date</b>	<b>12.04.2005</b>
		<b>Revision Date</b>	<b>13.04.2022</b>
		<b>Revision No</b>	<b>3</b>
		<b>Page No</b>	<b>8 /10</b>

**Legal Warning**

All information contained in this safety data sheet has been prepared based on the best of our experience, knowledge and reliable sources available at the time of preparation. While meticulous attention is paid to the accuracy of the information, there is no guarantee of the perfection or accuracy of the information contained in this document. The advice contained in this document may not be adequate for all individuals and/or situations. It is the responsibility of the users to evaluate the product, to use it safely and to comply with the laws and regulations regarding the issues related to this use. The wording used in this document shall not be considered an authorization, recommendation, or license for work performed without a valid license. Polinas Plastik San. ve Tic. Inc. will not be held responsible.

---